














Heating Room Thermostat Catalogue

Item No.	Picture	Description
FC285 Black		Measure range:0 ~ 50 Celsius
		Temperature control Accuracy :+/-0.5 Celsius
		Power supply: 90-240VAC (24V optional)
		Child lock, Open window detect, Frost or overheat protection
		Sensor type:NTC B=3380 10K
		Weekly programe (5+2/6+1/7)
		Control mode:3A / 16A heating
		White or black color optional
FC285 White		Measure range:0 ~ 50 Celsius
		Temperature control Accuracy :+/-0.5 Celsius
		Power supply: 90-240VAC (24V optional)
		Child lock, Open window detect, Frost or overheat protection
		Sensor type:NTC B=3380 10K
		Weekly programe (5+2/6+1/7)
		Control mode:3A / 16A heating
		White or black color optional
HY08WE/WW-02		Measure range:0 ~ 40 Celsius
		Temperature control Accuracy :+/-0.5 Celsius
		Power supply: 90-240VAC (24V optional)
		Child lock, Open window detect, Frost or overheat protection
		Sensor type:NTC B=3380 10K
		Weekly programe (5+2/6+1/7)
		Control mode:3A / 16A heating
		White or black color optional
HY08WE/WW-04		Measure range:0 ~ 40 Celsius
		Temperature control Accuracy :+/-1 Celsius
		Power supply: 90-240VAC (24V optional)
		Child lock, Open window detect, Frost or overheat protection
		Sensor type:NTC B=3380 10K@25Celsius
		Weekly programe (5+2/6+1/7)
		Control mode:3A / 16A heating
		White or black color optional
Wi-Fi function optional		

<p>HY09RF</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 90-240VAC (24V optional)</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>White or black color optional</p> <p>Wireless heating thermostat</p>
<p>ST-C26</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC (24V optional)</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>White or black color optional</p> <p>Wi-Fi function optional</p>
<p>ST-C28</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>White or black color optional</p> <p>Wi-Fi function optional</p>
<p>ST-C17</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>Body material: Antiflaming PC</p> <p>Wi-Fi function optional</p>

<p>HY609WW/WE</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 90-240VAC (24V optional)</p> <p>Child lock, Open window detect, Frost or overheat protection</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>White or black color optional</p> <p>Wi-Fi function optional</p>
<p>ST-C18</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A heating</p> <p>Body material: Antiflaming PC</p> <p>Wi-Fi function optional</p>
<p>ST-C07</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC (24V optional)</p> <p>Power consumption:<1W</p> <p>A and B frame for optional.</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Weekly programe programe (5+2/6+1/7)</p> <p>Control mode:3A / 16A /30A heating</p> <p>Body material: Antiflaming PC</p>
<p>ST-C03</p>		<p>Measure range:0 ~ 40 Celsius</p> <p>Temperature control Accuracy :+/-1 Celsius</p> <p>Power supply: 85-250VAC (24V optional)</p> <p>Power consumption:<1W</p> <p>Sensor type:NTC B=3380 10K@25Celsius</p> <p>Control mode:3A / 16A heating</p> <p>Body material: Antiflaming PC</p> <p>Remote function: optional</p>
<p>ST-C06</p>		<p>Measure range:10 ~ 30 Celsius</p> <p>Power supply:220VAC 50/60Hz</p> <p>Control mode:3A heating</p> <p>Temperature sensor:Inflated film case</p> <p>LED and ON/OFF swich</p>

Note: The backlight color: Blue / Green / White optional